



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 100 MΩ Min
- Di electric Withstanding Voltage : 500V AC RMS 60 Seconds

MATERIAL

- Insulator : Nylon PA9T, UL94V-0
- Contact : Phosphor Bronze
- Contact Plated : Tin Plated or Gold Plated
- Operation Temperature : - 25°C to + 85°C

SPWMK01R1X1TB4 CONTACTS	DIMENSIONS		
	A	B	C
2	1.00	2.40	4.00
3	2.00	3.40	5.00
4	3.00	4.40	6.00
5	4.00	5.40	7.00
6	5.00	6.40	8.00
7	6.00	7.40	9.00
8	7.00	8.40	10.00
9	8.00	9.40	11.00
10	9.00	10.40	12.00
11	10.00	11.40	13.00
12	11.00	12.40	14.00
13	12.00	13.40	15.00
14	13.00	14.40	16.00
15	14.00	15.40	17.00
16	15.00	16.40	18.00
17	16.00	17.40	19.00
18	17.00	18.40	20.00
19	18.00	19.40	21.00
20	19.00	20.40	22.00
21	20.00	21.40	23.00
22	21.00	22.40	24.00

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD

三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@tpnts6.seed.net.tw E-MAIL: Cen88888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
FUFU	WENDY	2011/03/31	1:1

SPWMK01R1X1TB4

圖號 701-XXS-1.0
DRAWING NO.