



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 2 Ampere AC/DC
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1000 MΩ Min
- Dielectric Withstanding Voltage : 800V AC RMS 60 Seconds
- Voltage Rating : 100V DC

MATERIAL

- Insulator : Nylon 46 UL94V-0
 - Contact : Phos. Bronze
 - Contact Plated : Tin Plated or Gold Plated
- Operation Temperature : - 25°C to + 85°C

SPXWA03R1XXTB4	DIMENSIONS	
CONTACTS	A	B
02	2.0	8.0
03	4.0	10.0
04	6.0	12.0
05	8.0	14.0
06	10.0	16.0
07	12.0	18.0
08	14.0	20.0
09	16.0	22.0
10	18.0	24.0
11	20.0	26.0
12	22.0	28.0
13	24.0	30.0

UNIT: mm

CENTRONIC PRECISION ELECTRONIC COMPANY

MORLINKOM TECHNOLOGY LTD

三川精密電子有限公司

魔林科技有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen88888@gmail.com

繪圖 DRAWN BY
FU-FU

日期 DATE
2011/03/31

核對 CHECKED BY
WENDY

比例 SCALE
1:1

SPXWA03R1XXTB4

圖號 701-XX-H03

DRAWING NO.