



### SPECIFICATIONS

#### ELECTRICAL

- Contact Current Rating : 3 Amperes AC/DC
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1000 MΩ Min
- Dielectric Withstanding Voltage : 800V AC RMS 60 Seconds
- Voltage Rating : 250V AC/DC

#### MATERIAL

- Insulator : Nylon 66 UL94V-0
- Contact : Brass
- Contact Plated : Tin Plated
- Operation Temperature : - 25°C to + 85°C

| PXWR2XXTB4A2 CONTACTS | DIMENSIONS |       |
|-----------------------|------------|-------|
|                       | A          | B     |
| 06                    | 4.00       | 7.90  |
| 08                    | 6.00       | 9.90  |
| 10                    | 8.00       | 11.90 |
| 12                    | 10.00      | 13.90 |
| 14                    | 12.00      | 15.90 |
| 16                    | 14.00      | 17.90 |
| 18                    | 16.00      | 19.90 |
| 20                    | 18.00      | 21.90 |
| 22                    | 20.00      | 23.90 |
| 24                    | 22.00      | 25.90 |
| 26                    | 24.00      | 27.90 |
| 28                    | 26.00      | 29.90 |
| 30                    | 28.00      | 31.90 |
| 32                    | 30.00      | 33.90 |

UNIT : mm

**CENTRONIC PRECISION ELECTRONIC COMPANY**  
 三川精密電子有限公司  
 TEL: 886-2-2686-8788  
 E-MAIL: Centron@tpts6.seed.net.tw

**MORLINKOM TECHNOLOGY LTD**  
 魔林科技有限公司  
 FAX: 886-2-2686-0018  
 E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUFU  
 核對 CHECKED BY WENDY  
 日期 DATE 2012/09/18  
 比例 SCALE 1:1

**PXWR2XXTB4A2**

圖號 701-2XX-03  
 DRAWING NO.