



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 500 MΩ Min

- Dielectric Withstanding Voltage : 500V AC RMS 60 Seconds
- Voltage Rating : 150V DC

MATERIAL

- Insulator : Nylon PA9T, UL94V-0
- Contact : Phosphor Bronze
- Contact Plated : Tin Plated or Gold Plated

Operation Temperature : - 35°C to + 85°C

SPKX02S2XXGB1	DIMENSIONS		
CONTACTS	A	B	C
10	5.00	8.09	7.50
20	11.25	14.34	13.75
30	17.50	20.59	20.00
40	23.75	26.84	26.25
50	30.00	33.09	32.50

UNIT : mm

MORLINTOM TECHNOLOGY

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
FUFU	WENDY	1:1	2011/03/31

SPKX02S2XXGB1

圖號 **700-240-VX2**
DRAWING NO.