



MATERIAL

- Insulator : LCP UL 94V-0
- Contact : Phosphor Bronze
- Contact Plated : Gold / Tin Selective Plated
- Board Lock : Brass · Tin Plated
- Rivet : Brass · Nickel Plated
- Shell : Steel · Nickel Plated

SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Voltage Rated : 40V AC

MECHANICAL

- Insertion Force : 4.5Kg
- Extraction Force : 1 Kg
- Durability 100 Cycles Min
- Operation Temperature : - 20°C to + 85°C

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	FUFU	2011/03/30	
CHECKED BY	WENDY	比例	SCALE
		1:1	

DVISP24+6GB4#1

圖號 545-24+6DVI
 DRAWING NO.