



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 5 Amperes
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 1000 V AC RMS 60 Seconds
- Rated Voltage : 250V DC

MATERIAL

- Insulator : PBT UL 94V-0
 - Contact : Brass
 - Contact Plated : Gold / Tin Selective Plated
 - Board Lock : Copper Alloy , Tin Plated
 - Square Rivet : Copper Alloy , Nickel Plated
 - Shell : Steel , Nickel Plated
 - Shell Bracket : Brass , Nickel Plated
- Operation Temperature : - 40°C to + 105°C



CONTACTS	A	B	C
9	0.38	0.13	0.25
(D)	16.33	24.99	30.81
15	24.66	33.32	39.14
(F)	25	38.38	47.04
(G)	54.48	63.50	69.32
(H)			

VERTICAL DIMENSION BETWEEN CONNECTORS	D	E
X	0.25	0.38
Y	15.88	28.42
Z	19.05	31.60
	22.86	35.41

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL: Centron@pts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY
FU-FU
核對 CHECKED BY
WENDY

日期 DATE
2011/11/29
比例 SCALE
1:1

DDPPXXYSBIX Y ZZ

圖號 369-XXB-X/Y/Z
DRAWING NO.