



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Voltage Rated : 40V AC

MATERIAL

- Insulator : LCP UL 94V-0
 - Contact : Phosphor Bronze
 - Contact Plated : Gold / Tin Selective Plated
 - Board Lock : Brass, Tin Plated
 - Rivet : Brass, Nickel Plated
 - Shell : Steel, Nickel Plated
- ### MECHANICAL
- Insertion Force : 4.5Kg
 - Extraction Force : 1 Kg
 - Durability 100 Cycles Min
 - Operation Temperature : - 20°C to + 85°C

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL: Centron@tpits6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2011/03/30

DVISR24GB4#1

圖號

545-24DV1

核對 CHECKED BY

WENDY

比例 SCALE

1:1

DRAWING NO.