



SPECIFICATION

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 25 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 1000 V AC RMS 60 Seconds

MATERIAL

- Insulator : PBT UL 94V-0
- Contact : Brass
- Contact Plated : Selective Gold Over Copper Plated
- Shell : Steel
- Shell Plated : Tin , Nickel OR Zinc Plated

MECHANICAL

- Mating cycles : 3000 Cycles Min.
- Operation Temperature : - 40°C to + 105°C

DPPXXSB4#1 CONTACTS	DIMENSIONS		
	A	B	C
9	16.92	24.99	30.81
15	25.25	33.32	39.25
25	38.96	47.04	53.04
37	55.42	63.50	69.50
50	53.02	61.11	66.93

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY
 三川精密電子有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD
 魔林科技有限公司
 繪圖 DRAWN BY FUJU
 核對 CHECKED BY WENDY
 日期 DATE 2011/03/30
 比例 SCALE 1:1

DPPXXSB4#1
 圖號 DRAWING NO. 471-XX