



SPECIFICATION

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 25 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 1000 V AC RMS 60 Seconds

MATERIAL

- Insulator : PBT UL 94V-0
- Contact : Brass
- Contact Plated : Selective Gold Over Copper Plated
- Shell : Steel
- Shell Plated : Tin , Nickel OR Zinc Plated

MECHANICAL

- Mating cycles : 3000 Cycles Min.
- Operation Temperature : - 40°C to + 105°C

| HDSXXXSB1#1 | DIMENSIONS | | | |
|-------------|------------|-------|-------|------|
| CONTACTS | A | B | C | D |
| 15 | 16.33 | 24.99 | 30.81 | 2.29 |
| 26 | 24.66 | 33.32 | 39.25 | 2.29 |
| 44 | 38.38 | 47.04 | 53.04 | 2.29 |
| 62 | 54.84 | 63.50 | 69.50 | 2.41 |

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

| | | | |
|------|------------|-----|-------|
| 繪圖 | DRAWN BY | 日期 | DATE |
| 核對 | CHECKED BY | 比例 | SCALE |
| FUFU | WENDY | 1:1 | |

HDSXXXSB1#1

圖號 501-XX
 DRAWING NO.