



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 2 Ampere
- Contact Resistance : 15 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Di electric Withstanding Voltage : 1000 V AC RMS 60 Seconds

MATERIAL

- Insulator : PBT UL94V-0.
- Contact : Brass
- Contact Plated : Gold Plated , Selective Gold Over Nickel
- Shell : Steel
- Shell Plated : Nickel Plated
- Screw : Brass
- Screw Plated : Nickel Plated

Operation Temperature : - 40°C to + 105°C

HDRPPXXSB2#3		DIMENSIONS				
CONTACTS	A	B	C	D	E	
15	16.33	24.99	30.80	7.04	2.29	
26	24.66	33.32	39.25	6.88	2.29	
44	38.38	47.04	53.04	6.88	2.29	
62	54.84	63.50	69.32	6.99	2.41	

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788

E-MAIL: Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX:886-2-2686-0018

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2011/03/29

核對 CHECKED BY

WENDY

比例 SCALE

1:1

圖號

541-XX-01

DRAWING NO.

HDRPPXXSB2#3

DRAWING NO.