



| HDRDPXXSBI#4 | DIMENSIONS | | | | |
|--------------|------------|-------|-------|------|------|
| CONTACTS | A | B | C | D | E |
| 15 | 16.92 | 24.99 | 30.80 | 7.04 | 2.29 |
| 26 | 25.25 | 33.32 | 39.25 | 6.88 | 2.29 |
| 44 | 38.96 | 47.04 | 53.04 | 6.88 | 2.29 |
| 62 | 55.42 | 63.50 | 69.32 | 6.99 | 2.41 |

UNIT: mm

SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 2 Ampere
- Contact Resistance : 15 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Di electric Withstanding Voltage : 1000 V AC RMS 60 Seconds

MATERIAL

- Insulator : PBT UL94V-0.
 - Contact : Brass
 - Contact Plated : Gold Plated , Selective Gold Over Nickel
 - Shell : Steel
 - Shell Plated : Nickel Plated
 - Screw : Brass
 - Screw Plated : Nickel Plated
- Operation Temperature : - 40°C to + 105°C

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL: Centron@pts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

核對 CHECKED BY

WENDY

日期 DATE

2011/03/29

比例 SCALE

1:1

HDRDPXXSBI#4

圖號

551-XX-01

DRAWING NO.