



| DFSXXSB2A3 CONTACTS | DIMENSIONS |       |       |
|---------------------|------------|-------|-------|
|                     | A          | B     | C     |
| 9                   | 16.33      | 24.99 | 30.81 |
| 15                  | 24.66      | 33.30 | 39.20 |
| 25                  | 38.38      | 47.04 | 53.05 |
| 37                  | 54.84      | 63.50 | 69.40 |

UNIT : mm

### SPECIFICATIONS

#### ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1000 MΩ Min
- Dielectric Withstanding Voltage : 1000 V AC RMS 60 Seconds
- Voltage Rating : 250VAC

#### MATERIAL

- Insulator : PBT UL 94V-0
- Contact : Brass
- Contact Plated : Gold Plated
- Clinch Nut : Brass, Nickel Plated
- Shell : Steel, Tin Plated Over Copper
- Screwlock : Brass, Nickel Plated
- Operation Temperature : - 55°C to + 105°C

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD  
 三川精密電子有限公司 魔林科技有限公司  
 TEL:886-2-2686-8788 FAX:886-2-2686-0018  
 E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUFU  
 核對 CHECKED BY WENDY  
 日期 DATE 2011/03/30  
 比例 SCALE 1:1

圖號 340-XX  
 DRAWING NO. DFSXXSB2A3