



DFPXXSB2A3	DIMENSIONS		
CONTACTS	A	B	C
9	16.92	24.99	30.81
15	25.25	33.30	39.20
25	38.96	47.04	53.05
37	55.42	63.50	69.40

UNIT : mm

### SPECIFICATIONS

#### ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1000 MΩ Min
- Dielectric Withstanding Voltage : 1000 V AC RMS 60 Seconds
- Voltage Rating : 250VAC

#### MATERIAL

- Insulator : PBT UL 94V-0
- Contact : Brass
- Contact Plated : Gold Plated
- Clinch Nut : Brass · Nickel Plated
- Shell : Steel · Tin Plated Over Copper
- Screwlock : Brass · Nickel Plated
- Operation Temperature : - 55°C to + 105°C

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD  
 三川精密電子有限公司 魔林科技有限公司  
 TEL:886-2-2686-8788 FAX:886-2-2686-0018  
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUFU  
 核對 CHECKED BY WENDY  
 日期 DATE 2011/03/30  
 比例 SCALE 1:1

圖號 350-XX  
 DRAWING NO. DFPXXSB2A3