



DFPXXSB2A2	DIMENSIONS		
CONTACTS	A	B	C
9	18.05	25.00	30.50
15	26.35	33.32	39.00
25	40.95	47.04	53.08
37	55.60	63.50	69.25

UNIT : mm

SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
 - Contact Resistance : 20 mΩ Max
 - Insulator Resistance : 1000 MΩ Min
 - Dielectric Withstanding Voltage : 1000 V AC RMS 60 Seconds
 - Voltage Rating : 250VAC
- #### MATERIAL
- Insulator : PBT UL 94V-0
 - Contact : Brass
 - Contact Plated : Selective Plated
 - Operation Temperature : - 55°C to + 105°C

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUJFU
 核對 CHECKED BY WENDY

日期 DATE 2011/03/30
 比例 SCALE 1:1

DFPXXSB2A2

圖號 350-XX-01
 DRAWING NO.