



DFSXXXSB2A2 CONTACTS	DIMENSIONS		
	A	B	C
9	16.00	25.00	30.50
15	24.27	33.32	39.00
25	38.22	47.04	53.08
37	54.65	63.50	69.25

UNIT : mm

SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 20 m Ω Max
- Insulator Resistance : 1000 M Ω Min
- Di electric Withstanding Voltage : 1000 V AC RMS 60 Seconds
- Voltage Rating : 250VAC

MATERIAL

- Insulator : PBT UL 94V-0
- Contact : Brass
- Contact Plated : Selective Plated
- Operation Temperature : - 55 $^{\circ}$ C to + 105 $^{\circ}$ C

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUFU
 核對 CHECKED BY WENDY
 日期 DATE 2011/03/30
 比例 SCALE 1:1

圖號 340-XX-01
 DFSXXXSB2A2
 DRAWING NO.