



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 2A 12V DC / 0.5A 30V DC
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 100 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

MECHANICAL

- Insertion & Extraction Force :
Initial : 0.3 To 3.0 Kgs
- After life test : 0.2 To 3.0 Kgs
- Life test (20-30 cycle/minute) 500 cycles unloading

UNIT : mm

MORLINTKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINTKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@tpsts6.seed.net.tw E-MAIL: Cen8888@gmail.com

| | | | |
|------------|----------|------------|-------|
| 繪圖 | DRAWN BY | 日期 | DATE |
| 核對 | FUFU | 2009/10/26 | |
| CHECKED BY | WENDY | 比例 | SCALE |
| | | 1:1 | |

BPJ-324

圖號 851-25
DRAWING NO.