



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 0.5 Ampere
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 500 MΩ Min
- Dielectric Withstanding Voltage : 200 V AC RMS 60 Seconds
- Voltage Rating : 50 V

MATERIAL

- Insulator : LCP6807, Cover : LCP6130
 - Contact : Phosphor Bronze
 - Plated : Gold Plated, Tin Plated, Selective Plated
- Operation Temperature : - 25°C to + 85°C

| DIMENSIONS CONTACTS | DIMENSIONS | | | | DIMENSIONS CONTACTS | DIMENSIONS | | | |
|---------------------|------------|-------|-------|-------|---------------------|------------|-------|-------|-------|
| | A | B | C | D | | A | B | C | D |
| 4 | 1.50 | 6.00 | 7.50 | 2.62 | 28 | 13.50 | 18.00 | 19.50 | 14.62 |
| 5 | 2.00 | 6.50 | 8.00 | 3.12 | 29 | 14.00 | 18.50 | 20.00 | 15.12 |
| 6 | 2.50 | 7.00 | 8.50 | 3.62 | 30 | 14.50 | 19.00 | 20.50 | 15.62 |
| 7 | 3.00 | 7.50 | 9.00 | 4.12 | 31 | 15.00 | 19.50 | 21.00 | 16.12 |
| 8 | 3.50 | 8.00 | 9.50 | 4.62 | 32 | 15.50 | 20.00 | 21.50 | 16.62 |
| 9 | 4.00 | 8.50 | 10.00 | 5.12 | 33 | 16.00 | 20.50 | 22.00 | 17.12 |
| 10 | 4.50 | 9.00 | 10.50 | 5.62 | 34 | 16.50 | 21.00 | 22.50 | 17.62 |
| 11 | 5.00 | 9.50 | 11.00 | 6.12 | 35 | 17.00 | 21.50 | 23.00 | 18.12 |
| 12 | 5.50 | 10.00 | 11.50 | 6.62 | 36 | 17.50 | 22.00 | 23.50 | 18.62 |
| 13 | 6.00 | 10.50 | 12.00 | 7.12 | 37 | 18.00 | 22.50 | 24.00 | 19.12 |
| 14 | 6.50 | 11.00 | 12.50 | 7.62 | 38 | 18.50 | 23.00 | 24.50 | 19.62 |
| 15 | 7.00 | 11.50 | 13.00 | 8.12 | 39 | 19.00 | 23.50 | 25.00 | 20.12 |
| 16 | 7.50 | 12.00 | 13.50 | 8.62 | 40 | 19.50 | 24.00 | 25.50 | 20.62 |
| 17 | 8.00 | 12.50 | 14.00 | 9.12 | 41 | 20.00 | 24.50 | 26.00 | 21.12 |
| 18 | 8.50 | 13.00 | 14.50 | 9.62 | 42 | 20.50 | 25.00 | 26.50 | 21.62 |
| 19 | 9.00 | 13.50 | 15.00 | 10.12 | 43 | 21.00 | 25.50 | 27.00 | 22.12 |
| 20 | 9.50 | 14.00 | 15.50 | 10.62 | 44 | 21.50 | 26.00 | 27.50 | 22.62 |
| 21 | 10.00 | 14.50 | 16.00 | 11.12 | 45 | 22.00 | 26.50 | 28.00 | 23.12 |
| 22 | 10.50 | 15.00 | 16.50 | 11.62 | 46 | 22.50 | 27.00 | 28.50 | 23.62 |
| 23 | 11.00 | 15.50 | 17.00 | 12.12 | 47 | 23.00 | 27.50 | 29.00 | 24.12 |
| 24 | 11.50 | 16.00 | 17.50 | 12.62 | 48 | 23.50 | 28.00 | 29.50 | 24.62 |
| 25 | 12.00 | 16.50 | 18.00 | 13.12 | 49 | 24.00 | 28.50 | 30.00 | 25.12 |
| 26 | 12.50 | 17.00 | 18.50 | 13.62 | 50 | 24.50 | 29.00 | 30.50 | 25.62 |
| 27 | 13.00 | 17.50 | 19.00 | 14.12 | | | | | |

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

MORLINKOM TECHNOLOGY LTD

繪圖 DRAWN BY FUFU

日期 DATE 2011/03/09

三川精密電子有限公司
TEL:886-2-2686-8788 FAX:886-2-2686-0018

魔林科技有限公司

E-MAIL: Centron@tpits6.seed.net.tw E-MAIL: Cen8888@gmail.com

核對 CHECKED BY WENDY

比例 SCALE 1:1

0.5FPCSXTBAS

圖號

768-XX-S

DRAWING NO.