



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min

- Dielectric Withstanding Voltage : 1,000V AC RMS 60 Seconds

MECHANICAL

- Insertion Force : 340 g Max / Pin
- Extraction Force : 50 g Min / Pin

MATERIAL

- Insulator : PBT, UL 94V-0
- Contact : Phosphor Bronze
- Contact Plated : Tin Plated

Operation Temperature : - 25°C to + 85°C

ICSAXTBIAC	DIMENSION			
	CONTACTS	A	B	C
24	27.94	30.38	10.06	7.62
28	33.02	35.46	10.06	7.62
32	38.10	40.54	10.06	7.62

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUFU
 核對 CHECKED BY WENDY

日期 DATE 2008/12/15
 比例 SCALE 1:1

ICSAXTBIAC

圖號 00-XX-02
 DRAWING NO.