



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 1,000V AC RMS 60 Seconds

MECHANICAL

- Insertion Force : 340 g Max / Pin
 - Extraction Force : 50 g Min / Pin
- MATERIAL**
- Insulator : PBT, UL 94V-0
 - Contact : Phosphor Bronze
 - Contact Plated : Tin Plated
- Operation Temperature : - 25°C to + 85°C

ICSAXXTBIAE	DIMENSION			
	CONTACTS	A ^{+0.10} _{-0.10}	B ^{+0.12} _{-0.12}	C ^{+0.15} _{-0.15} D ^{+0.30} _{-0.30}
24	27.94	30.38		
28	33.02	35.46		
32	38.10	40.54		
40	48.26	50.70	17.68	15.24
42	50.80	53.24		
48	58.42	60.86		

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUFU
 核對 CHECKED BY WENDY
 日期 DATE 2008/12/15
 比例 SCALE 1:1

ICSAXXTBIAE

圖號 00-XX
 DRAWING NO.