



MORL INKOM

ICSRXSB1AC	DIMENSION				
	CONTACTS	A	B	C	D
20	+0 -0.20	+0.20 -0.20	+0 -0.20	+0 -0.20	+0.20 -0.20
24	22.86	25.40	27.94	30.48	10.16
28	27.94	30.48	33.02	35.56	7.62
32	33.02	35.56	38.10	40.64	

UNIT : mm

SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 10 mΩ Max
- Insulator Resistance : 5,000 MΩ Min
- Operating Voltage : 100V AC/DC
- Dielectric Withstanding Voltage : 1,000V AC RMS 60 Seconds

MECHANICAL

- Insertion Force : 250 g / Pin
- Extraction Force : 50 g / Pin
- Mechanical Life Cycle : 200 Min
- Insertion Force : 340 Grams Max
- Extraction Force : 50 Grams MIN

MECHANICAL

- Insulator : PBT , UL 94V-0
 - Contact : Beryllium Copper ~ BeCu
 - Contact Plated : Selective Gold Plated Over Nickel
 - Pin(Outer Sleeve) : Brass , Tin Plated
- OPERATING TEMPERATURE : - 40°C to + 105°C

CENTRONIC PRECISION ELECTRONIC COMPANY MORL INKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUFU
 核對 CHECKED BY WENDY

日期 DATE 2008/12/16
 比例 SCALE 1:1

ICSRXSB1AC

圖號 DRAWING NO. 20-XX-02