



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 10 mΩ Max
- Insulator Resistance : 5,000 MΩ Min
- Operating Voltage : 100V AC/DC
- Dielectric Withstanding Voltage : 1,000V AC RMS 60 Seconds

MECHANICAL

- Insertion Force : 250 g / Pin
- Extraction Force : 50 g / Pin
- Mechanical Life Cycle : 200 Min
- Insertion Force : 340 Grams Max
- Extraction Force : 50 Grams MIN

MECHANICAL

- Insulator : PBT , UL 94V-0
 - Contact : Beryllium Copper (BeCu)
 - Contact Plated : Selective Gold Plated Over Nickel
 - Pin(Outer Sleeve) : Brass , Tin Plated
- OPERATING TEMPERATURE : - 40°C to + 105°C

ICSRXXSBIIE	DIMENSION			
CONTACTS	A ⁺⁰ _{-0.20}	B ^{+0.20} _{-0.20}	C ⁺⁰ _{-0.20}	D ^{+0.20} _{-0.20}
40	48.26	50.80		
42	50.80	53.34	17.78	
48	58.42	60.96		15.24

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	FUFU	2008/12/16	
CHECKED BY	WENDY	比例	SCALE
		1:1	

ICSRXXSBIIE 圖號 20-XX
 DRAWING NO.