



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 15 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds

MATERIAL

- Insulator : PBT, UL94V-0
- Contact : Brass or Phosphor Bronze
- Insulator Resistance : 1000MΩ Min. at DC 500 Volts.
- Contact Plated : Gold or Tin Over Nickel Plated
- Operation Temperature : - 40°C to + 105°C

HIDXSXBIAI CONTACTS	DIMENSIONS			HIDS CONTACTS	DIMENSIONS		
	A	B	C		A	B	C
06	4.00	5.00	11.20	36	34.00	35.00	41.20
08	6.00	7.00	13.20	38	36.00	37.00	43.20
10	8.00	9.00	15.20	40	38.00	39.00	45.20
12	10.00	11.00	17.20	44	42.00	43.00	49.20
14	12.00	13.00	19.20	48	46.00	47.00	53.20
16	14.00	15.00	21.20	50	48.00	49.00	55.20
18	16.00	17.00	23.20	54	52.00	53.00	59.20
20	18.00	19.00	25.20	56	54.00	55.00	61.20
22	20.00	21.00	27.20	60	58.00	59.00	65.20
24	22.00	23.00	29.20	62	60.00	61.00	67.20
26	24.00	25.00	31.20	64	62.00	63.00	69.20
28	26.00	27.00	33.20	68	66.00	67.00	73.20
30	28.00	29.00	35.20	80	78.00	79.00	85.20
32	30.00	31.00	37.20	100	98.00	99.00	105.20
34	32.00	33.00	39.20				

UNITS mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788

E-MAIL: Centron@pts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX:886-2-2686-0018

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2009/05/15

核對 CHECKED BY

WENDY

比例 SCALE

1:1

HIDXSXBIAI

圖號

285-XX

DRAWING NO.