



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 0.5 Ampere
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 250 V AC RMS 60 Seconds

MATERIAL

- Insulator : PBT, UL94V-0
 - Contact : Brass or Phosphor Bronze
 - Contact Plated : Gold or Tin Over Nickel Plated
 - Cable : Pitch 0.635mm Flat Cable
- Operation Temperature : - 40°C to + 105°C

HHSXSBIBI	DIMENSIONS	
CONTACTS	A	B
06	2.54	8.01
08	3.81	9.28
10	5.08	10.55
12	6.35	11.82
14	7.62	13.09
16	8.89	14.36
20	11.43	16.90
22	12.70	18.17
26	15.24	20.71
30	17.78	23.25
34	20.32	25.79
40	24.31	29.60
44	26.67	32.14
50	30.48	35.95
60	36.83	42.30
68	41.91	47.38
80	49.53	55.00

UNIT : mm

MORL INKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY

MORL INKOM TECHNOLOGY LTD

三川精密電子有限公司

魔林科技有限公司

TEL:886-2-2686-8788 FAX:866-2-2686-0018

E-MAIL: Centron@ipts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2011/03/09

核對 CHECKED BY

WENDY

比例 SCALE

1:1

HHSXSBIBI

圖號 286-XX-01

DRAWING NO.