



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Cable : Pitch 0.635mm Flat Cable

MATERIAL

- Insulator : PBT, UL94V-0
- Contact : Brass or Phosphor Bronze
- Contact Plated : Gold Plated Over Nickel
- Solder Area -- Nickel Plated
- Operation Temperature : - 40°C to + 105°C

DPGBX1TBI CONTACTS	DIMENSIONS	
	A	B
08	7.62	15.45
10	10.16	17.95
14	15.24	23.05
16	17.78	25.50
18	20.32	28.12
20	22.86	30.68
24	27.94	35.80
28	33.02	40.81
34	40.64	51.03
40	48.26	56.15

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
FUFU	WENDY	2009/02/05	1:1

DPGBX1TBI

圖號 781-XX
DRAWING NO.