



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds

MATERIAL

- Insulator : PBT, UL94V-0
- Contact : Brass or Phosphor Bronze
- Contact Plated : Gold or Tin Over Nickel Plated
- Cable : Pitch 1.27mm Flat Cable
- Operation Temperature : - 55°C to + 105°C

| CONTACTS | DIMENSIONS | | | |
|----------|------------|-------|-------|--------|
| | A | B | C | D |
| 20 | 11.43 | 18.52 | 15.99 | 7.300 |
| 26 | 15.24 | 22.33 | 19.80 | 9.205 |
| 32 | 19.05 | 26.14 | 23.60 | 11.110 |
| 34 | 20.32 | 27.41 | 24.88 | 11.745 |
| 40 | 24.13 | 31.22 | 28.68 | 13.650 |
| 50 | 30.48 | 37.57 | 35.04 | 16.825 |
| 52 | 31.75 | 38.84 | 36.30 | 17.460 |
| 60 | 36.83 | 43.92 | 41.40 | 20.000 |
| 68 | 41.91 | 49.00 | 46.22 | 22.540 |
| 80 | 49.53 | 56.62 | 54.09 | 26.350 |
| 100 | 62.23 | 69.32 | 66.79 | 32.700 |

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD

三川精密電子有限公司 魔林科技有限公司

TEL:886-2-2686-8788 FAX:866-2-2686-0018

E-MAIL: Centron@ipts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUFU
核對 CHECKED BY WENDY

日期 DATE 2010/01/18
比例 SCALE 1:1

HHIDSXSBJAI

圖號 287-XX

DRAWING NO.