



SPECIFICATIONS ELECTRICAL

- Contact Current Rating : 1 Amperes
 - Contact Resistance : 30 mΩ Max
 - Insulator Resistance : 3,000 MΩ Min
 - Dielectric Withstanding Voltage : 500V AC RMS 60 Seconds
- MATERIAL**
- Insulator : PBT Glass Reinforced, Reated UL 94V-0
 - Contact : Brass
 - Plated : Mating Area -- Gold Over Nickel
Solder Area -- Tin Over Nickel
- Operation Temperature : - 40°C to + 150°C

CEPXXSBIBI	DIMENSION		
CONTACTS	A	B	C
10	10.16	22.36	13.04
14	15.24	27.44	18.12
16	17.78	29.98	20.66
20	22.86	35.06	25.74
26	30.48	42.68	33.36
34	40.64	52.84	43.52
40	48.26	60.46	51.14
50	60.96	73.16	63.84

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen8888@gmail.com

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY
FUJU

FUJU

核對 CHECKED BY
WENDY

WENDY

日期 DATE
2010/03/10

2010/03/10

比例 SCALE
1:1

1:1

CEPXXSBIBI

圖號

290-XX-01

DRAWING NO.