



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 2 Amperes
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 5,000 MΩ Min
- Di electric Withstanding Voltage : AC 500 V RMS 60 Seconds

MATERIAL

- Insulator : Nylon-9T
- Contact : Brass
- Contact Plated : Gold Plated (Standard) 、Tin Plated

Operation Temperature : - 40°C to + 150°C
Selective Plated

HLRXXGBI CONTACTS	DIMENSION		
	A	B	C
06	4.00	13.20	12.10
08	6.00	15.20	14.10
10	8.00	17.20	16.10
12	10.00	19.20	18.10
14	12.00	21.20	20.10
16	14.00	23.20	22.10
18	16.00	25.20	24.10
20	18.00	27.20	26.10
22	20.00	29.20	28.10
24	22.00	31.20	30.10
26	24.00	33.20	32.10
30	28.00	37.20	36.10
34	32.00	41.20	40.10
40	38.00	47.20	46.10
44	42.00	51.20	50.10
50	48.00	57.20	56.10
60	58.00	67.20	66.10
64	62.00	71.20	70.10

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY WENDY
 核對 CHECKED BY WENDY
 日期 DATE 2011/09/20
 比例 SCALE 1:1

HLRXXGBI

圖號 DRAWING NO. 335-XX