



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 5,000 MΩ Min
- Dielectric Withstanding Voltage : 1,000V AC RMS 1 Min

MATERIAL

- Insulator : PBT , UL 94V-0 , Color/Black
- Contact : Brass
- Contact Plated : Gold Plated (Standard) 、Tin Plated

Operati on Temperature : - 40°C to + 150°C

SLHSXXGB1 CONTACTS	DIMENSION	
	A	B
06	5.08	12.58
08	7.62	15.20
10	10.16	17.74
12	12.70	22.74
14	15.24	25.28
16	17.78	27.82
18	20.32	30.36
20	22.86	32.90
24	27.94	37.98
26	30.48	40.52
30	35.56	43.06
34	40.64	50.68
40	48.26	58.30
44	53.34	63.38
50	60.96	71.00
60	73.66	83.82
64	78.74	88.78

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@tpnts6.seed.net.tw E-MAIL: Cen88888@gmail.com

繪圖 DRAWN BY 日期 DATE
 FUFU 2011/02/21
 核對 CHECKED BY 比例 SCALE
 WENDY 1:1

SLHSXXGB1 圖號 322-XX
 DRAWING NO.