



## SPECIFICATION

### ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500V AC RMS 60 Seconds

### MECHANICAL

- Contact Retention Force : 900g/Pin Min
- Insertion Force : 500g/Pin Max
- Extraction Force : 100g/Pin Min

### MATERIAL

- Insulator : PBT, UL94V-0
- Contact : Brass
- Contact Plated : Gold Plated , Tin Plated
- Operation Temperature : - 45°C to + 105°C

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788

E-MAIL: Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX:886-2-2686-0018

E-MAIL: Cen8888@gmail.com

繪圖

DRAWN BY  
REMUS

核對 CHECKED BY  
WENDY

日期 DATE  
2011/11/02

比例 SCALE  
1:1

比例 SCALE  
1:1

MSA02GB1

圖號

46-02

DRAWING NO.