



SPECIFICATION

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 20 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500V AC RMS 60 Seconds

MECHANICAL

- Contact Retention Force : 900g/Pin Min
- Insertion Force : 500g/Pin Max
- Extraction Force : 100g/Pin Min

MATERIAL

- Insulator : NYLON 66
- Contact : Brass

- Contact Plated : Gold Plated , Tin Plated
- Operation Temperature : - 45°C to + 105°C

UNIT : mm

MORLINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY

MORLINKOM TECHNOLOGY LTD

三川精密電子有限公司

魔林科技有限公司

TEL:886-2-2686-8788

FAX:886-2-2686-0018

E-MAIL: Centron@tp6.seed.net.tw

E-MAIL: Cen8888@gmail.com

繪圖

DRAWN BY

日期

2011/11/02

圖號

70-02

比例

1:1

核對

CHECKED BY

SCALE

MSS02GB1

DRAWING NO.

WENDY

1:1

DRAWING NO.