



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : Tin Plated -- 20 mΩ Max
Gold Plated -- 10 mΩ Max
- Insulator Resistance : 5,000 MΩ Min
- Dielectric Withstanding Voltage : 1000V AC RMS 60 Seconds

MECHANICAL

- Insertion Force : 5 OZ Max (0.25"SQ Pin)
- Withdrawal Force : 1 OZ Min (0.25"SQ Pin)
- Retention Force : Over 70 OZ

MATERIAL

- Insulator : PBT, UL94V-0 , Color White
- Contact Plated : Gold Plated , Tin Plated , Selective Plated

Operation Temperature : - 55°C to + 105°C

UNIT : mm

TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788

E-MAIL: Centron@pts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX:866-2-2686-0018

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

核對 CHECKED BY

WENDY

日期 DATE

2009/09/25

比例 SCALE

1:1

PFS2XXGB1

圖號

170-XX

DRAWING NO.