



SPECIFICATIONS
ELECTRICAL

- Contact Current Rating : 1 Amperes
- Contact Resistance : 15 mΩ Max
- Insulator Resistance : 5,000 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds

MATERIAL

- Insulator : Nylon-6T , UL 94-0
- Contact : Brass
- Contact Plated : Gold Plated , Tin Plated , Selective Plated
- Operation Temperature : - 40°C to + 105°C

P	2.5	2.0	1.5	1.0
---	-----	-----	-----	-----

A = mm
B = mm
TTL = mm

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL: Centron@tpsts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2011/02/21

核對 CHECKED BY

WENDY

比例 SCALE

1:1

HHPHS1XKGB1HX

圖號 865PXX-HXX

DRAWING NO.

TECHNOLOGY LTD.