



P	3.0	2.7	2.5	2.0	1.7	1.5	1.0
---	-----	-----	-----	-----	-----	-----	-----

A = mm

B = mm

C = mm

SPECIFICATIONS
ELECTRICAL

- Contact Current Rating : 1 Amperes
 - Contact Resistance : 15 mΩ Max
 - Insulator Resistance : 5,000 MΩ Min
 - Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- MATERIAL**
- Insulator : Nylon-6T, UL 94-0
 - Contact : Brass
 - Contact Plated : Gold Plated, Tin Plated, Selective Plated
- Operation Temperature : - 40°C to + 105°C

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD

三川精密電子有限公司 三川精密電子有限公司
 TEL: 886-2-2686-8788 FAX: 886-2-2686-0018
 E-MAIL: Centron@tpnts6.seed.net.tw E-MAIL: Cen88888@gmail.com

繪圖 DRAWN BY FU-FU
 核對 CHECKED BY WENDY

日期 DATE 2009/03/11
 比例 SCALE 1:1

SHHPHS2XKGB1HX

圖號 866S-XX-HXX
 DRAWING NO.

SHINDO GY LTD.