



P	2.5	2.0	1.5	1.0
---	-----	-----	-----	-----

A =  $\text{mm}$   
 B =  $\text{mm}$   
 TTL =  $\text{mm}$

UNIT: mm

**SPECIFICATIONS**

**ELECTRICAL**

- Contact Current Rating : 1 Amperes
- Contact Resistance : 15 mΩ Max
- Insulator Resistance : 5,000 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds

**MATERIAL**

- Insulator : Nylon-6T , UL 94-0
  - Contact : Brass
  - Contact Plated : Gold Plated , Tin Plated , Selective Plated
- Operation Temperature : - 40°C to + 105°C

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD

三川精密電子有限公司 魔林科技有限公司  
 TEL: 886-2-2686-8788 FAX: 886-2-2686-0018  
 E-MAIL: Centron@tp6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	FUFU	2009/03/11	
CHECKED BY	WENDY	比例	SCALE
		1:1	

HHPHS2XKGB1HX

圖號 866PXX-HXX  
 DRAWING NO.

MORLINKOM TECHNOLOGY LTD.