



PLADXXTB9A2 PLADXXTB1A1	DIMENSIONS			
	A±0.15	B±0.15	C±0.15	D±0.15
CONTACTS				
20	5.08	15.50	5.08	15.50
28	7.62	18.04	7.62	18.04
32	7.62	18.04	10.16	20.54
44	12.70	23.48	12.70	23.48
52	15.24	25.88	15.24	25.88
68	20.32	31.04	20.32	31.04
84	25.40	36.04	25.40	36.04

UNIT: mm

SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Amper
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 VAC RMS 60 sec.

MATERIAL

- Insulator : PBT · UL 94V-0 (Standard) · PPS · UL 94V-0
- Contact : Phosphor Bronze
- Contact Plated : Gold Plated 、 Tin Plated
Selective Plated

Operation Temperature : - 55°C to + 105°C

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL: 886-2-2686-8788

E-MAIL: Centron@tppts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX: 886-2-2686-0018

E-MAIL: Cen88888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2009/06/15

PLADXXTB9A2

圖號

260-XX-01

核對 CHECKED BY

WENDY

比例 SCALE

1:1

PLADXXTB1A1

DRAWING NO.

260-XX