



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Amper
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 VAC RMS 60 sec.

MATERIAL

- Insulator : PPS , UL 94V-0
- Contact : Phosphor Bronze
- Contact Plated : Gold Plated , Tin Plated
- Selective Plated

Operation Temperature : - 55°C to + 105°C

PLASXXTB9B2	DIMENSIONS							
CONTACTS	A±0.2	B±0.2	C±0.2	D±0.2	E±0.3			
20	5.08	15.24	5.08	15.24	16.70			
28	7.62	17.78	7.62	17.78	20.30			
32	7.62	18.20	10.16	20.74	22.76			
44	12.70	23.28	12.70	23.28	28.05			
52	15.24	25.74	15.24	25.74	31.13			
68	20.32	30.82	20.32	30.82	38.31			
84	25.40	35.90	25.40	35.90	45.50			

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788

E-MAIL: Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX:886-2-2686-0018

E-MAIL: Cen88888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2012/02/01

PLASXXTB9B2

圖號

270-XX-01

核對 CHECKED BY

WENDY

比例 SCALE

1:1

DRAWING NO.