



PLASXXTB9B5	DIMENSIONS			
CONTACTS	A±0.2	B±0.2	C±0.2	D±0.2
20	5.08	15.24	5.08	15.64
28	7.62	17.78	7.62	17.78
32	7.62	18.20	10.16	20.74
44	12.70	23.28	12.70	23.28
52	15.24	25.40	15.24	25.40
68	20.32	30.82	20.32	30.82
84	25.40	35.90	25.40	35.90

UNIT: mm

SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Amper
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 VAC RMS 60 sec.

MATERIAL

- Insulator : PPS , UL 94V-0
- Contact : Phosphor Bronze
- Contact Plated : Gold Plated , Tin Plated
- Selective Plated

Operation Temperature : - 55°C to + 105°C

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788

E-MAIL: Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX:886-2-2686-0018

E-MAIL: Cen8888@gmail.com

繪圖

DRAWN BY
FUJFU

日期
2009/11/05

PLASXXTB9B5

圖號

270-XX-05

核對
CHECKED BY
WENDY

比例
SCALE
1:1

DRAWING NO.