



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
 - Contact Resistance : 30 mΩ Max
 - Insulator Resistance : 500 MΩ Min
 - Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
 - Operating Voltage : 150V AC Max
- MATERIAL**
- Insulator : PBT UL94V-0 / NYLON PA9T (High Temperature)
 - Contact : Phosphor Bronze
 - Contact Plated : Gold Plated , Tin Plated , Selective Plated
 - Shield : Nickel Plated Brass Alloy

UNIT : mm

MORLINTKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY

MORLINTKOM TECHNOLOGY LTD

三川精密電子有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@tpts6.seed.net.tw

魔林科技有限公司
 E-MAIL: Cen88888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	FUFU	2011/03/30	
CHECKED BY	WENDY	比例	SCALE
		1:1	

RJ45R10P80GB1#1B

圖號 850-41
 DRAWING NO.