



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 500 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

MATERIAL

- Insulator : Thermoplastic UL94V-0
- Contact : 0.35mm Thickness Phosphor Bronze
- Contact Plated : Gold Plated , Tin Plated , Selective Plated

RHS/PCGBI#0	DIMENSIONS	
CONTACTS	A	B
4	7.65	11.4
6	10.16	13.4
8	11.43	15.5

UNIT : mm

MORLINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:886-2-2686-0018
 E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen88888@gmail.com

繪圖 DRAWN BY FUFU
 核對 CHECKED BY WENDY
 日期 DATE 2011/03/30
 比例 SCALE 1:1

RJ11S6P6CGBI#0

圖號 850-24
 DRAWING NO.