



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 500 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

MATERIAL

- Insulator : Thermoplastic UL94V-0
- Contact : 0.35mm Thickness Phosphor Bronze
- Contact Plated : Gold Plated , Tin Plated , Selective Plated

RHSPKGBI#5	DIMENSIONS		
CONTACTS	A	B	C
4	11.4	13.8	7.65
6	13.4	15.8	10.16
8	15.5	17.8	11.43

UNIT: mm

MORLINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL: 886-2-2686-8788

E-MAIL: Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX: 886-2-2686-0018

E-MAIL: Cen88888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	FUFU	2011/03/30	
CHECKED BY	WENDY	比例	SCALE
		1:1	

RJ11S6P6CGBI#5	圖號	850-29
RJ11S6P4CGBI#5	DRAWING NO.	850-34