



### SPECIFICATIONS

#### ELECTRICAL

- Contact Current Rating : 1.5 Amperes
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1000MΩ Min
- Di electric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

#### MATERIAL

- Insulator : PBT UL94V-0
- Contact : Phosphor Bronze
- Contact Plated : Gold Plated · Tin Plated · Selective Plated
- Shield : Nickel Plated Brass Alloy

#### MECHANICAL

- Insertion Force : 35Newtons Max
- Extraction Force : 10Newtons Min
- Durability(life test) : 1500 cycles

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

MORLINKOM TECHNOLOGY LTD

三川精密電子有限公司

魔林科技有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2011/03/30

核對 CHECKED BY

WENDY

比例 SCALE

1:1

圖號

851-24

DRAWING NO.

DRAWING NO.