



**SPECIFICATIONS**

**ELECTRICAL**

- Contact Current Rating : 1.5 Amperes
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1000MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

**MATERIAL**

- Insulator : PBT UL94V-0
- Contact : Phosphor Bronze

- Contact Plated : Gold Plated · Tin Plated · Selective Plated
- Shield : Nickel Plated Brass Alloy

**MECHANICAL**

- Insertion Force : 35Newtons Max
- Extraction Force : 10Newtons Min
- Durability (life test) : 1500 cycles

UNIT : mm

**CENTRONIC PRECISION ELECTRONIC COMPANY** MORLINKOM TECHNOLOGY LTD  
 三川精密電子有限公司 魔林科技有限公司  
 TEL:886-2-2686-8788 FAX:886-2-2686-0018  
 E-MAIL: Centron@tpts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY  
 核對 CHECKED BY  
 FUFU WENDY

日期 DATE  
 比例 SCALE  
 2011/03/30 1:1

RJ45DR8P8C2X4GB1#2C

圖號 DRAWING NO.  
 850-44