



SPECIFICATIONS
ELECTRICAL

- Contact Current Rating : 1 Ampere
 - Contact Resistance : 30 mΩ Max
 - Insulator Resistance : 500 MΩ Min
 - Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
 - Operating Voltage : 150V AC Max
- MATERIAL**
- Insulator : Thermoplastic UL94V-0
 - Contact : 0.35mm Thickness Phosphor Bronze
 - Contact Plated : Gold Plated , Tin Plated , Selective Plated
 - Shield : Nickel Plated Brass Alloy
- UNIT : mm**

MORLINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL: 886-2-2686-8788 FAX: 886-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖 DRAWN BY FUJU	日期 DATE 2011/03/30	圖號 850-28
核對 CHECKED BY WENDY	比例 SCALE 1:1	DRAWING NO.
RJ45R8P8CGB1#1D		