



## SPECIFICATIONS

### ELECTRICAL

- Contact Current Rating : 1 Ampere
  - Contact Resistance : 30 m $\Omega$  Max
  - Insulator Resistance : 500 M $\Omega$  Min
  - Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
  - Operating Voltage : 150V AC Max
- MATERIAL**
- Insulator : Thermoplastic UL94V-0
  - Contact : 0.35mm Thickness Phosphor Bronze
  - Contact Plated : Gold Plated, Tin Plated, Selective Plated
  - Shield : Nickel Plated Brass Alloy
- UNIT : mm**

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL: Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

E-MAIL: Cen88888@gmail.com

E-MAIL: Cen88888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
FUFU	WENDY	2011/03/30	1:1

RJ45R8P8CGB1#2B

圖號 850-39  
DRAWING NO.