



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Amperere
- Contact Resistance : 30 m Ω Max
- Insulator Resistance : 500 M Ω Min
- Di electric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Operating Voltage : 150V AC Max

MATERIAL

- Insulator : Thermoplastic UL94V-0
- Contact : 0.35mm Thickness Phosphor Bronze
- Contact Plated : Gold Plated · Tin Plated · Selective Plated
- Shield : Nickel Plated Brass Alloy

BASE PCB #4A	DIMENSIONS			
CONTACTS	A	B	C	D
6	13.9	15.8	10.16	13.65
8	15.9	17.8	11.43	15.43

UNIT : mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL: 886-2-2686-8788

E-MAIL: Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

FAX: 886-2-2686-0018

E-MAIL: Cen88888@gmail.com

繪圖 DRAWN BY

FUFU

日期 DATE

2011/03/30

核對 CHECKED BY

WENDY

比例 SCALE

1:1

圖號

850-26

DRAWING NO.