



### SPECIFICATIONS

#### ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 4 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Operating Voltage : 60V AC/DC

#### MATERIAL

- Insulator : PPS, UL 94V-0
- Contact : Brass
- Contact Plated : Gold Plated、Tin Plated

Operation Temperature : Gold Plated : - 55°C to + 125°C

Tin Plated : - 40°C to + 105°C

UNIT: mm

MORLINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY  
 三川精密電子有限公司  
 TEL: 886-2-26886-8788 FAX: 886-2-26886-0018  
 E-MAIL: Centron@pts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD  
 魔林科技有限公司  
 TEL: 886-2-26886-8788 FAX: 886-2-26886-0018  
 E-MAIL: Cent8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
	FUFU	1:1	2009/05/13
	WENDY		

MPPR1XXGB103

圖號 145-XX-G03  
 DRAWING NO.