



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 4 mΩ Max
- Insulator Resistance : 5,000 MΩ Min
- Operating Voltage : 60V AC/DC
- Dielectric Withstanding Voltage : 1,000V AC RMS 60 Seconds

MATERIAL

- Insulator : PPS, UL 94V-0
- Contact : Brass
- Contact Plated : Gold Plated、Tin Plated

Operation Temperature : Gold Plated : - 55°C to + 125°C

Tin Plated : - 40°C to + 105°C

UNIT: mm

CENTRONIC PRECISION ELECTRONIC COMPANY
 三川精密電子有限公司
 TEL:886-2-26886-8788 FAX:886-2-26886-0018
 E-MAIL:Centron@pts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD
 魔林科技有限公司
 TEL:886-2-26886-8788 FAX:886-2-26886-0018
 E-MAIL:Cent8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
	FUFU	2009/05/14	1:1
	WENDY		

MPR1XXGB102

圖號 145-XX-G02
 DRAWING NO.