



- ### SPECIFICATIONS
- #### ELECTRICAL
- Contact Current Rating : 3 Amperes
 - Contact Resistance : 20 mΩ Max
 - Insulator Resistance : 5,000 MΩ Min
 - Dielectric Withstanding Voltage : 1,000V AC RMS 60 Seconds
- #### MECHANICAL
- Insertion Force : 340 g Max / Per Pair
 - Extraction Force : 28 g Min / Per Pair
- #### MATERIAL
- Insulator : PBT, UL94V-0
 - Contact : Brass
 - Plated : Mating Area -- Gold Over Nickel
Solder Area -- Tin Over Nickel
- Operation Temperature : - 55°C to + 105°C

UNIT : mm

MORLINKOM TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY

MORLINKOM TECHNOLOGY LTD

三川精密電子有限公司

魔林科技有限公司

TEL:886-2-2686-8788 FAX:866-2-2686-0018

E-MAIL: Centron@ipts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
FUFU	WENDY	2009/09/25	1:1

ECS98SBIA1

圖號 240-98
DRAWING NO.