



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 500 V AC RMS 60 Seconds
- Voltage Rating : 250V AC

MECHANICAL

- Insertion Force : 230 g Max / Per Pair
 - Withdrawal Force : 15 g Min / Per Pair
 - Retention Force : 460 g Min / Pin
- MATERIAL**
- Insulator : LCP · Color White
 - Contact : Copper Alloy
 - Plated : Mating Area -- Selected Gold Over Nickel
- Operation Temperature : - 55°C to + 85°C

UNIT : mm

PCB LAYOUT

TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINKOM TECHNOLOGY LTD
 三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:866-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
FUFU	WENDY	2010/01/25	1:1

PCI120PTB4-R

圖號 **245-120-PCI-R**
 DRAWING NO.