



SPECIFICATIONS

ELECTRICAL

- Contact Current Rating : 3 Amperes
- Contact Resistance : 30 mΩ Max
- Insulator Resistance : 500 MΩ Min
- Dielectric Withstanding Voltage : 2,000V AC RMS 60 Seconds
- Voltage Rating : 300 VAC
- Wire Range : 12-22 AWG

MATERIAL

- Insulator : PA66 , Black , UL94V-0
- Contact : Brass , Tin Plated
- Screws : Steel , M4 , Zinc Plated

MECHANICAL

- Torque : 18 kg-cm
- Operation Temperature : - 40°C to +105°C

UNIT : mm

MORLINTKON TECHNOLOGY LTD.

CENTRONIC PRECISION ELECTRONIC COMPANY MORLINTKON TECHNOLOGY LTD

三川精密電子有限公司 魔林科技有限公司
 TEL:886-2-2686-8788 FAX:866-2-2686-0018
 E-MAIL: Centron@pts6.seed.net.tw E-MAIL: Cen8888@gmail.com

繪圖	DRAWN BY	日期	DATE
核對	CHECKED BY	比例	SCALE
FUFU	WENDY	2011/03/29	1:1

TBC02TB1

圖號 854-05
 DRAWING NO.